

**I CLAIM:**

1. A combination for attaching to a headrest of a vehicle, said combination comprising:

5 a carrying case including a housing and a casing each having a side portion secured together, and each having two side portions and an upper portion openably secured together with a fastening device,

said housing and said casing each including a chamber formed in an inner portion thereof for receiving objects, and each including an outer portion superposable with each other,

10 an electric facility receivable in said chamber of said housing, and

said casing including at least one first fastening band attached to said upper portion thereof, and at least one second fastening band attached to either of said side portions thereof, for engaging onto  
15 the headrest of the vehicle, and for solidly attaching and retaining said carrying case and said electric facility to the headrest of the vehicle.

2. The combination as claimed in claim 1, wherein said housing includes a pocket provided in said lower portion thereof to  
20 define a space therein, and to receive a lower portion of said electric facility.

3. The combination as claimed in claim 2, wherein said housing further includes a resilient fastening belt attached to said upper portion thereof, to resiliently clamp an upper portion of said  
25 electric facility, and to retain said electric facility in said chamber of said housing.

4. The combination as claimed in claim 1, wherein each of said

at least one first fastening band and said at least one second fastening band includes a hook and loop fastening device attached to a free end portion thereof for fastening said carrying case to the headrest of the vehicle.

5           5. The combination as claimed in claim 1, wherein said casing includes a compartment attached to said outer portion thereof for receiving objects therein.

          6. The combination as claimed in claim 1, wherein said casing includes at least one third fastening band attached to said lower  
10       portion thereof, and engageable with said at least one first fastening band thereof, to attach said carrying case to the headrest of the vehicle.

          7. A combination for attaching to a headrest of a vehicle, said combination comprising:

15           a carrying case including a housing and a casing each having a side portion secured together, and each having two side portions and an upper portion openably secured together with a fastening device,

          said housing and said casing each including a chamber formed in an inner portion thereof for receiving objects, and each including  
20       an outer portion superposable with each other,

          an electric facility receivable in said chamber of said housing, and

          said casing including at least one first fastening band attached to said upper portion thereof, and at least one second and at least  
25       one third fastening bands attached to said side portions thereof respectively, for engaging onto the headrest of the vehicle, and for solidly attaching and retaining said carrying case and said electric

facility to the headrest of the vehicle.

8. The combination as claimed in claim 7, wherein said housing includes a pocket provided in said lower portion thereof to define a space therein, and to receive a lower portion of said electric  
5 facility.

9. The combination as claimed in claim 8, wherein said housing further includes a resilient fastening belt attached to said upper portion thereof, to resiliently clamp an upper portion of said electric facility, and to retain said electric facility in said chamber of  
10 said housing.

10. The combination as claimed in claim 7, wherein each of said at least one first and said at least one second and said at least one third fastening bands includes a hook and loop fastening device attached to a free end portion thereof for fastening said carrying  
15 case to the headrest of the vehicle.

11. The combination as claimed in claim 7, wherein said casing includes a compartment attached to said outer portion thereof for receiving objects therein.

12. The combination as claimed in claim 7, wherein said casing  
20 includes at least one fourth fastening band attached to said lower portion thereof, and engageable with said at least one first fastening band thereof, to attach said carrying case to the headrest of the vehicle.

25